

3875 Embassy Parkway Fairlawn, OH 44333

855.753.5474 koroseal.com



As we see hard lines give way to soft undulating curves, our new Sandscape design re-creates the pleasure we feel walking on the rolling sandy beaches or laying on our back while watching the clouds float across the sky, creating positive emotions.

	US UNITS	METRIC UNIT	ΓS	
Total Weight	20.0 oz. PLY 13.3 oz. PSY	620 g PLM 451 g PSM		
Roll Width	52" – 54"	132 cm - 137 cn	n	
Backing	Non-Woven			
Tensile (Minimum)	$50 \times 55 \text{ lb}_{\text{f}}$	222 x 245 N		
Tear (Minimum)	$25 \ x \ 25 \ lb_f$	111 x 111 N		
Federal Spec.	CCC-W-408D,	CCC-W-408D, Type II		
WA Spec.	WA-101, Type	WA-101, Type II		
ASTM F-793	Category V, Ty	Category V, Type II		
Fire Testing	NFPA 255 (AS'	NFPA 101 [®] Life Safety Code [®] NFPA 255 (ASTM E-84, CAN S102M)) Tunnel Test ¹ Class A Rating		
	NFPA 286 Corr	ner Burn Test ²		
		Meets requirements for Flame Spread, Smoke Developed and Flashover		
CE Certification	EU classificatio	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 0135	California 01350 - Meets emission requirements for schools and offices		
Repeat Vertical Horizontal Nominal Patte Match Inform		26.5"		
1 When applied to GRC board with A-	848-B adhesive 2 When applied to	5/8" Type-X-Gypsum board with A-848-B ac	dhesive	

Available in 11 Colorways

Tuxedo SP21-01 Causeway SP21-12 Fog SP21-02 *Metal SP21-14 Blush SP21-06 Admiral SP21-16 Major Grey SP21-07 Seaforam SP21-19 Graphite SP21-08 Salt SP21-21

Cobblestone SP21-11

^{*}This decorative metallic wallcovering should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.